

SINOLTECH ENERGY LIMITED SHANDONG SINOLTECH INTERNATIONAL CO., LTD



INTEGRITY. HIGH BRIGHTNESS. EASY-INSTALL

STANDARD ALL-IN-ONE SOLAR LIGHT SERIES 5 Years Product Warranty

MODEL SELECTION:

- SNSTY-2100
- SNSTY-2120

SINOLTECH SERVICE:

- OEM and ODM service
- Dialux report
- Instruction(or video) if you don't know how to install
- If not work, exchange spare part or new product, free of charge under warranty 5 years
- APP, cellular phone programming function (for 18W-120W SNSTY Series)



sinol version 4.0.apk

ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 100W, 120W

100W

SNSTY-2100 with APP



Description
100W
Bridgelux 45
102
10000~11000LM
DC 12V
DC 18V
IP65
78
90 mm
120 degree
>0.95
3000~6000
50000 hrs
-30°C~+60°C
15~90%RH



SOLAR LIGHT TECHNICAL DATA


Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	130W
Solar Cell Brand	SOLARWORLD GERMANY
Battery Capacity	Lithium 80 AH
Lamp Lumens(LM)	10000~11000LM
Mounting Height	9-11 m
Mounting Distance	35~40m for one-way road, 70-80m for two-way road, intercross distance
Working Method	Timer control, APP


Packing Detail:

Product size: 1570*460*45mm Product Weight: 22 KG

Pack size:

1650*530*120mm Pack Volume: 0.10CBM Gross Weight: 26KG





TECHNICAL DATA SHEET

ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 100W, 120W

120 W





報節	in H	I
-		
		1100



LED TECHNICAL DATA	
Item	Description
LED Rated Power(W)	120W
LED Brand	Bridgelux 45
LED NO.(pcs)	120
Lamp Lumens(LM)	12000~13000LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	90 mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA		
Item	Description	
Main Material	Aluminum Alloy+Solar PV	
Solar Panel Power(W)	150W	
Solar Cell Brand	SOLARWORLD GERMANY	
Battery Capacity	Lithium 88 AH	
Lamp Lumens(LM)	12000~13000LM	
Mounting Height	9-12 m	
Mounting Distance	35~40m for one-way road, 70~80m for two-way road, intercross distance	
Working Method	Timer control, APP	

Packing Detail:

Product size/Weight: 1670*460*45mm/23KG Pack size/Volume: 1750*530*120mm 0.12CBM

Gross Weight: 27KG

