



SINOLTECH ENERGY LIMITED

SHANDONG SINOLTECH INTERNATIONAL CO., LTD



SINOLTECH

INTEGRITY . HIGH BRIGHTNESS . EASY-INSTALL

STANDARD ALL-IN-ONE SOLAR LIGHT SERIES
5 - Years Product Warranty

MODEL SELECTION:

- SNSTY-240
- SNSTY-250
- SNSTY-260
- SNSTY-270
- SNSTY-280

SINOLTECH SERVICE:

- OEM and ODM service
- Dialux report
- Instruction(or video) if you don't know how to install
- If not work, exchange spare part or new product, free of charge under warranty 5 years
- APP, cellular phone programming function available




SINOLTECH.apk

ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 40W, 50W, 60W, 70W, 80W

40W

SNSTY-240 with APP



Packing Detail:



Product size/Weight: 1210*340*45mm/16.0 KG
 Pack size/Volume: 1320*400*200mm/0.10CBM
 Gross Weight: 18KG

LED TECHNICAL DATA

Item	Description
LED Rated Power(W)	40W
LED Brand	Bridgelux 45
LED NO.(pcs)	42
Lamp Lumens(LM)	4000~4300LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	60 ~ 110 mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA

Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	70W
Solar Cell Brand	Solarworld Germany
Battery Capacity	Lithium 36 AH
Lamp Lumens(LM)	4000~4300LM
Mounting Height	6-7.5 m
Mounting Distance	30~35m for one-way road, 60-70m for two-way road, intercross distance
Working Method	Timer control, Motion sensor, APP



TECHNICAL DATA SHEET

ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 40W, 50W, 60W, 70W, 80W

50 W

SNSTY-250 with APP



LED TECHNICAL DATA



Item	Description
LED Rated Power(W)	50W
LED Brand	Bridgelux 45
LED NO.(pcs)	50
Lamp Lumens(LM)	5000~5500LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	60 ~ 110 mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA

Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	85W
Solar Cell Brand	Solarworld Germany
Battery Capacity	Lithium 44 AH
Lamp Lumens(LM)	5000~5500LM
Mounting Height	7-8 m
Mounting Distance	30~35m for one-way road, 60-70m for two-way road, intercross distance
Working Method	Timer control, Motion sensor, APP

Packing Detail:

Product size/Weight: 1210*340*45mm/16.0 KG
 Pack size/Volume: 1320*400*200mm/0.10 CBM
 Gross Weight: 19KG



ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 40W, 50W, 60W, 70W, 80W

60 W

SNSTY-260 with APP



LED TECHNICAL DATA



Item	Description
LED Rated Power(W)	60W
LED Brand	Bridgelux 45
LED NO.(pcs)	60
Lamp Lumens(LM)	6000~7000LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	60~110mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA

Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	85W
Solar Cell Brand	Solarworld Germany
Battery Capacity	Lithium 44 AH
Lamp Lumens(LM)	6000~7000LM
Mounting Height	7-8 m
Mounting Distance	30-35m for one-way road, 60-70m for two-way road, intercross distance
Working Method	Timer control, Motion sensor, APP

Packing Detail:

Product size/Weight: 1200*340*45mm/18.0 KG
 Pack size/Volume: 1345*400*200mm/0.11CBM
 Gross Weight: 19KG



TECHNICAL DATA SHEET 4

ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 40W, 50W, 60W, 70W, 80W

70W

SNSTY-270 with APP



LED TECHNICAL DATA



Item	Description
LED Rated Power(W)	70W
LED Brand	Bridgelux 45
LED NO.(pcs)	81
Lamp Lumens(LM)	7500~8000LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	60~110mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA

Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	90 W
Solar Cell Brand	Solarworld Germany
Battery Capacity	Lithium 50 AH
Lamp Lumens(LM)	7500~8000LM
Mounting Height	7-9 m
Mounting Distance	35~40m for one-way road, 70~80m for two-way road, intercross distance
Working Method	Timer control, Motion sensor, APP

Packing Detail:

Product size/Weight: 1210*460*45mm/21.0 KG
 Pack size/Volume: 1345*500*200mm/0.135CBM
 Gross Weight: 23KG



ALL IN ONE SOLAR STREET LIGHT

STANDARD MODELS: 40W, 50W, 60W, 70W, 80W

80W

SNSTY-280 with APP



LED TECHNICAL DATA

Item	Description
LED Rated Power(W)	80W
LED Brand	Bridgelux 45
LED NO.(pcs)	81
Lamp Lumens(LM)	8500~9000LM
Output Voltage	DC 12V
Input Voltage	DC 18V
Waterproof Degree	IP65
CRI	78
Suitable for pole diameter	60~110mm
LED beads Irritation angle	120 degree
Illumination efficiency	>0.95
CCT	3000~6000
LED life time	50000 hrs
Working Temperature	-30°C~+60°C
Working Humidity	15~90%RH

SOLAR LIGHT TECHNICAL DATA

Item	Description
Main Material	Aluminum Alloy+Solar PV
Solar Panel Power(W)	100 W
Solar Cell Brand	Solarworld Germany
Battery Capacity	Lithium 60 AH
Lamp Lumens(LM)	8500~9000LM
Mounting Height	8-9 m
Mounting Distance	35~40m for one-way road, 70~80m for two-way road, intercross distance
Working Method	Timer control, Motion sensor, APP



Packing Detail:

Product size/Weight: 1210*460*45mm/22.0 KG
 Pack size/Volume: 1345*500*200mm/0.135CBM
 Gross Weight: 24KG

